

Tellabs® 8110 Network Terminating Unit (CTU-S)

Overview

The Tellabs® 8110 Network Terminating Unit (CTU-S) is a Network Terminating Unit (NTU) that uses ETSI HDSL-based technology. The Tellabs 8110 NTU (CTU-S) has a maximum symmetrical data rate of 4,544 Kbps and it has AC, DC and remote power feed options.

The Tellabs 8110 NTU (CTU-S) is connected to the Tellabs® 8100 Managed Access System with the HCE modules (HCE-2M-1P, HCE-2M-2P) of the GMH unit or HCQ module of the QMH unit, which can be used in the Tellabs® 8140 Midi Node, Tellabs® 8150 Basic Node, Tellabs® 8160 Accelerator Node A111 or the Tellabs® 8170 Cluster Node.

The Tellabs 8110 NTU (CTU-S) is configured and monitored with the Tellabs® 8000 Network Manager. The Tellabs 8110 NTU (CTU-S) does not require any on-site configuration. However, a handheld VT100 terminal can be connected into the Tellabs 8110 NTU (CTU-S) to obtain the monitoring and status information.

Features and Benefits

Applications

The Tellabs 8110 NTU (CTU-S) high-speed modem is primarily designed for managed serial data access with fast and easy installation. With a G.704 interface it is also suitable for connecting mobile base stations or PBXs to the rest of the transmission network.

Specifications

Line Interface Features

When the line and DTE are connected, the Tellabs 8110 NTU (CTU-S) will automatically create a connection to the Tellabs 8100 system.

Signal encoding and impedance

- 2B1Q, 135 ohms

Transmit level (dBm)

- 13.5 dBm

Line bit rates (Kbps)

- 592, 1,168 and 2,320 Kbps

Connection

- 1-pair (2-wire)
- 2-pair (4-wire)

Estimated maximum cable** length

- 5.1 km @ 2,320 Kbps line rate
- 7.0 km @ 1,168 Kbps line rate
- 7.6 km @ 592 Kbps line rate

** 0.5 mm/40 nF/km, no noise

Line monitoring

- Carrier detection, signal level indication, CRC monitoring online, noise margin. End-to-end CRC with 8 Kbps external channel

Other features

- 1+1 Protection (Backup) of the copper line, power off indication (“dying gasp”)

Operating modes

- 1-pair mode
 - (1 x 2,320 Kbps, 1 x 1,168 Kbps, 1 x 592 Kbps)
- 2-pair mode
 - (2 x 2,320 Kbps, 2 x 1,168 Kbps, 2 x 592 Kbps, data split between the pairs)
- 1+1 backup mode
 - (2 x 2,320 Kbps, 2 x 1,168 Kbps, 2 x 592 Kbps, one line redundant with the other)

Connector type

- RJ-45



Figure 1. Tellabs® 8110 Network Terminating Unit (CTU-S)

Unit Construction

The Tellabs 8110 NTU (CTU-S) is housed in a compact plastic case suitable for tabletop use. LEDs on the front indicate the powering, line, and DTE status. The X.21, V.35 or G.703 DTE interface is integrated as well as the RS-232 interface suitable for VT100 terminal.

DTE Interface

One integrated DTE interface is included in Tellabs 8110 NTU (CTU-S)

G.703 DTE Interface

DTE interface bit rate

- 2,048 Kbps

Connector types

- Selectable with Tellabs 8000 manager:
 - SMB coaxial 75 ohms
 - 9-pin female D-connector 120 ohms

Signal coding

- HDB3

Transmit timing

- Co-directional

Output pulse amplitude

- 2.37 V @ 75 ohms and 3.0 V @ 120 ohms

V.35 DTE Interface

DTE interface bit rates

- n x 64 Kbps (64-4,544 Kbps), Tellabs 8100 system mode

Connector type

- 34-pin female connector, ISO 2593

Circuit levels

- Data and clock signals: V.35
- Control signals: V.28

Interface circuits

- 102, 103, 104, 105, 106, 107, 108, 109, 113, 115, 140, 141, 142

Transmit timing

- 113, 115, 113/115 meso

X.21 DTE Interface

DTE interface bit rates

- n x 64 Kbps (64-4,544 Kbps), Tellabs 8100 system mode

Connector type

- 15-pin D-connector, ISO 4903

Circuit levels

- X.27

Interface circuits

- T, C, R, I, G, S, X

Transmit timing

- S, X

Test Interface

Terminal rates

- 9600 bps

Connector type

- 6-pin RJ-connector

Circuit levels

- V.28 (RS-232)

Interface circuits

- 102, 103, 104

Transmit timing

- Asynchronous

Dimensions (width x depth x height)

195 mm x 180 mm x 45 mm, Weight 560 g

Power Supply

- Tellabs 8110 NTU (CTU-S) V.35/X.21:
 - 100-240 VAC
- Tellabs 8110 NTU (CTU-S) G.703:
 - -48 V DC, 55-110 V remote power or AC with adapter

Power Consumption

- <5 W

Standards

Performance

- ETS TS 101 135 (2000)

Safety

- EN60950:1992 (A1:1993, A2:1993, A3 1995, A4 1997, A11:1997)

EMC

- EN300 386:2000

Environmental Conditions

Storage

- ETS 300 019-1-1:1992 Class 1.1
 - Temperature: -5° C to +45° C

Transportation

- ETS 300 019-1-2:1992 Class 2.3
 - Temperature: -40° C to +70° C

Operating conditions

- ETS 300 019-1-7:1992 Class 7.2
 - Normal conditions:
 - Temperature: -5° C to +45° C
 - Relative humidity: 5% to 95%

Versions

Unit

- Tellabs 8110 NTU (CTU-S) V.35
 - Power Supply
 - 100-240 VAC
 - DTE Interface
 - V.35 (ISO 2593 34-pin female)

Unit

- Tellabs 8110 NTU (CTU-S) X.21
 - Power Supply
 - 100-240 VAC
 - DTE Interface
 - X.21

Unit

- Tellabs 8110 NTU (CTU-S) G.703
 - Power Supply
 - DC or remote power feed, AC with adapter
 - DTE Interface
 - E1: 75 ohms
 - E1: 120 ohms

Ordering and Availability

This product is currently available. Contact your local Tellabs sales representative or regional office for more information.

North America

Tellabs
One Tellabs Center
1415 West Diehl Road
Naperville, IL 60563
U.S.A.
+1 630 798 8800
Fax: +1 630 798 2000

Asia Pacific

Tellabs
3 Anson Road
#14-01 Springleaf Tower
Singapore 079909
Republic of Singapore
+65 6215 6411
Fax: +65 6215 6422

Europe, Middle East & Africa

Tellabs
Abbey Place
24-28 Easton Street
High Wycombe, Bucks
HP11 1NT
United Kingdom
+44 870 238 4700
Fax: +44 870 238 4851

Latin America & Caribbean

Tellabs
1401 N.W. 136th Avenue
Suite 202
Sunrise, FL 33323
U.S.A.
+1 954 839 2800
Fax: +1 954 839 2828

Statements herein may contain projections or other forward-looking statements regarding future events, products, features, technology and resulting commercial or technological benefits and advantages. These statements are for discussion purposes only, are subject to change and are not to be construed as instructions, product specifications, guarantees or warranties. Actual results may differ materially.

The following trademarks and service marks are owned by Tellabs Operations, Inc., or its affiliates in the United States and/or other countries: TELLABS®, TELLABS and T symbol®, and T symbol®.

Any other company or product names may be trademarks of their respective companies.

© 2008 Tellabs. All rights reserved.
74.0995E Rev. D 10/08