



## SmartPocket™

### OLS-34/35/36 Optical Light Sources

The JDSU OLS-3x series consists of small and rugged optical light sources for quick, easy, and convenient field insertion loss measurement and continuity checks.

All JDSU sources are equipped with Auto- $\lambda$  and Multi- $\lambda$  functions compatible with any JDSU power meter. This one button operation provides a quick, simple, and error-free testing solution, which makes SmartPocket™ sources the ideal tools for daily field testing.

#### Pocket-Sized Light Sources for All Kind of Applications

SmartPocket optical light sources (OLS-3x) are ideal tools to complement the OLP-3x for insertion loss and continuity testing in both multimode and single-mode optical fiber networks. They offer a dedicated and cost-optimized solution for testing and troubleshooting optical fibers in the field.

- The OLS-34 covers LAN/WAN access and enterprise multimode networks with 850/1300 nm
- The OLS-35 covers all standard singlemode telecommunication network applications with 1310/1550 nm
- The OLS-36 quad-wavelength solution covers both multimode and single-mode wavelengths in one instrument

#### Key Benefits

- Cost-effective, rugged, and compact optical light sources
- Interchangeable connectors for maximum flexibility available
- Auto  $\lambda$  and TwinTest transmission modes
- 3 year calibration
- Combines up to 4 wavelengths in one instrument (SM+MM)

#### Applications

- Link insertion loss measurements and continuity checks
- Enterprise/LAN networks with 850/1300 nm multimode wavelengths capability
- Access and metro (LAN/WAN) networks with multimode and single-mode testing combinations
- Standard single-mode wavelengths for any telecom, CATV, and military application

### A Small Product with Big Capabilities!

Large, clear screen displays:

- Battery status with low level indicator
- Power mode (PERM, ECON)
- Output wavelength setting
- Output power in dBm
- Auto wavelength coding
- Tone generation



Rugged, shock resistant, and splash proof design

Four buttons for fast, easy operation

3-way powering

- AA dry
- AA rechargeable
- AC operation via micro USB

Two connector solutions offer more flexibility:

- Fixed adapters: FC, SC, LC
- Interchangeable adapters: FC, SC, ST, LC, DIN



SmartPocket OMK-3x optical test kits include an OLS-3x optical light source, an OLP-3x optical power meter, and accessories

## Technical Specifications

	<b>OLS-34 Multimode Light Source</b>	<b>OLS-35 Single-mode Light Source</b>	<b>OLS-36 Quad Light Source</b>
Source type	LED	Laser	LED/Laser
Laser safety	IEC 60825-1:2003 IEC 60825-1:2007	IEC 60825-1:2007	IEC 60825-1:2003 IEC 60825-1:2007
Fiber type	MM (50/125 $\mu\text{m}$ )	SM (9/125 $\mu\text{m}$ )	MM (50/125 $\mu\text{m}$ )/SM (9/125 $\mu\text{m}$ )
Optical interface type	PC/1 single port for all wavelengths	PC/1 single port for all wavelengths	PC/1 port for MM and 1 port for SM
Optical interface connectors	Interchangeable LC, FC, SC, ST, DIN	Fixed: LC, FC, SC Interchangeable LC, FC, SC, ST, DIN	Fixed: SC Interchangeable: LC, FC, SC, ST, DIN
Central wavelength	850 nm ( $\pm 20$ nm) 1300 nm ( $-20$ nm/ $+40$ nm)	1310 nm ( $\pm 20$ nm) 1550 nm ( $\pm 20$ nm)	850 ( $\pm 20$ nm) 1300 ( $-20$ nm/ $+40$ nm) 1310 ( $\pm 20$ nm) 1550 ( $\pm 20$ nm)
Spectral width <sup>1</sup>	<170 nm	<5 nm	<170 nm/<5 nm
Output power	$-20$ dBm <sup>2</sup>	$-7$ dBm	$-20$ dBm <sup>2</sup> / $-7$ dBm
Stability short term (15 min) <sup>3</sup>	$\pm 0.02$ dB	$\pm 0.02$ dB	$\pm 0.02$ dB
Stability long term (8h) <sup>3</sup>	$\pm 0.05$ dB	$\pm 0.05$ dB	$\pm 0.05$ dB
Tone generation	270 Hz, 1 kHz, 2 kHz	270 Hz, 1 kHz, 2 kHz	270 Hz, 1 kHz, 2 kHz
Auto $\lambda$ mode <sup>4</sup>	Yes	Yes	Yes
Multi $\lambda$ mode <sup>4</sup>	Yes (2 $\lambda$ s)	Yes (2 $\lambda$ s)	Yes (4 $\lambda$ s)
Launch conditions	CPR capability for MM launch conditions		CPR capability for MM launch conditions

1. FWHM.
2. Into a 50/125  $\mu\text{m}$  fiber.
3. After 20 minutes warm-up time, at ambient temperature range  $-10^{\circ}\text{C}$  to  $+55^{\circ}\text{C}$ ,  $\Delta T = \pm 0.3$  K.
4. With JDSU power meters.

## General Specifications

<b>Power Supply</b>	
Dry batteries	2 AA 1.5V
Rechargeable batteries	2 AA NiMH 1.2V
AC operation	Via micro USB and SNT-505
Battery life (CW) <sup>1</sup>	30 h (MM)/80 h (SM) Automatic power-off after 20 minutes
<b>Environmental Conditions</b>	
EMI/ESD	CE compliance
Electrical safety	EN 61010-1:2002
Recommended calibration interval	3 years
Operating temperature	$-10$ to $+60^{\circ}\text{C}$ / $+14$ to $+140^{\circ}\text{F}$
Storage temperature	$-40$ to $+70^{\circ}\text{C}$ / $-40$ to $+158^{\circ}\text{F}$
Dimensions (H x W x D)	30 x 80 x 150 mm/1.2 x 3.1 x 5.9 in
Weight	200 g/0.45 lb

1. Typical.

**Ordering Information**

Name/Description	Part Number
OLS-34 LED source 850/1300 nm, MM, interchangeable adapter	2303/01
OLS-35 laser source 1310/1550 nm, SM, interchangeable adapter	2303/11
OLS-35 laser source 1310/1550 nm, SM, fixed FC/PC adapter	2303/12
OLS-35 laser source 1310/1550 nm, SM, fixed SC/PC adapter	2303/13
OLS-35 laser source 1310/1550 nm, SM, fixed LC/PC adapter	2303/15
OLS-36 quad source 850/1300/1310/1550 nm, SM, MM, interchangeable adapter	2303/21
OLS-36 quad source 850/1300/1310/1550 nm, SM, MM, fixed SC/PC adapter	2303/23

Each product includes:

- 2 AA alkaline batteries
- Neck strap
- Belt bag

Name/Description	Part Number
<b>Optional Accessories</b>	
Fiber Cleaning Consumables Kit	FCR-CLN-01
NiMH rechargeable batteries, mignon AA, 1.2V (2 batteries required)	2237/90.02
SNT-505; universal AC power adapter, micro USB connector	2302/90.01
ST universal adapter	2150/00.32
DIN universal adapter	2150/00.50
FC universal adapter	2150/00.51
SC universal adapter	2150/00.58
LC universal adapter	2150/00.59



Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176

TestEquipmentDepot.com