

INTERRUTTORE
Circuit Breaker
Disjoncteur
Schalter
Interruptor

N^o

MODUL
N630



Made in Italy

NOMINALE

Rated normal current
Courant nominal
Nennstrom
Tension nominale
Nennspannung
Tension nominal

660V~
250V-

CORRENTE NOMINALE
Rated normal current
Courant nominal
Nennstrom

630A

Intensidad nominal
POTERE DI INTERRUZO.
Breaking capacity
Pouvoir de coupure
Schaltvermögen
Capacidad de ruptura

V	kA
220 - 40	P1 P2
380 - 30	20
440 - 25	
500 - 20	
660 - 16	
250 - 20	

Hz 50 - 60

CARICO-LOAD
CHARGE-LAST

F-800K 3P

ACE
5146.86-10

I

AA فرسودگی 500 lm lt. لنگر

lm کمپوزیت

۵۰

ACE
K E N
3C
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

INTERRUTTORE
Circuit Breaker
Disjoncteur
Schalter
Interruptor

MODUL
N630

N° _____



Made in Italy

Tensione nominale

Teksting: Nominale

Nennspannung

Tensión nominal

CORRENTE NOMINALE

Rated normal current

Courant nominal

Nennstrom

Intensidad nominal

POTERE DI INTERRUZZ.

Breaking capacity

Pouvoir de coupure

Schaltvermögen

Capacidad de ruptura

Hz 50 - 60

660V~
250V-

630A

V	KA
220 - 40	F1 F2
380 - 30	20
440 - 25	
500 - 20	
660 - 16	
250 - 20	

CARICO - LOAD
CHARGE - LAST

9Vod.9

F-600X 3P

ON PERPETUITÉ
Contract Products
Distributors
Sole
Representative

N°

MODEL
N 630



Made in Italy

TENSIONE NOMINALE

Nominal voltage
Nominale spannung
Nominalspannung
Tension nominal

660V ~
250V -

CORRENTE NOMINALE

Rated normal current
Courant nominal
Nennstrom
Intensidad nominal

630A

POTERE DI INTERRUZZ.
Breaking capacity
Pouvoir de coupure
Scherleistung
Capacidad de ruptura

Hz 50 - 60

V	KA
330 - 40	11.2
300 - 30	10
440 - 18	
300 - 20	
440 - 18	
330 - 20	

CARICO-LOAD
CHARGE-LAST

9Vot.9

F-600K 3P
110V 50/60Hz