


17175 - F18BXSPX35RS10PK

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse








CAUTIONS & WARNINGS

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-

Bulb

4-Pin (2G11) Base Equivalent Wattage (NOM) 65.0 W 20000.0 h Rated Life (NOM) Starting Temperature (MIN) 10.0 °C Mercury Content (NOM) 4.0 mg 176.9911 pg Picograms of Mercury (NOM) Primary Application Facilities;Retail

Display; Hospitality; Office; Restaurant; Wa

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1250.0 Mean Lumens (NOM) 1130.0 Nominal Initial Lumens per Watt 69.44444 (NOM) Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 82.0 (NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) Voltage (NOM) 58.0 Lamp Current (NOM) 0.375 A Current Crest Factor (MAX) 1.7

DIMENSIONS

Maximum Overall Length 10.500 in(266.7 mm) (MOL) (NOM) Nominal Length (NOM) 10.500 in(266.7 mm)

PRODUCT INFORMATION

Product Code 17175

Description F18BXSPX35RS10PK ANSI Code 60901-IEC-2218-2 Standard Package Master

Standard Package GTIN 10043168171752

Standard Package Quantity 40 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 40

Package

UPC 043168171755

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- · Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.